

CA-6 P

INTRUDER ALARM CONTROL PANEL

The **CA-6** control panel is designed for security of small facilities which do not require future expansion options of the system. The control panel can cooperate with external GSM/GPRS communication modules.

- up to 8 zones
 - support for NC, NO, EOL, 2EOL/NC and 2EOL/NO loop configurations
 - flexible selection of zone function
- additional control input
- 5 programmable outputs
- 2 partitions
- RS-232 port (TTL) - RJ type socket
- on-board PSTN telephone dialer for reporting, messaging and remote uploading/downloading
- system operation
 - LED keypad
 - remote operation by telephone (with optional **MST-1** module)
- system programming
 - local (LED keypad, PC connected to RS-232 port)
 - remote (PC communicating via modem)
- system codes
 - 1 master user code
 - up to 12 user codes
 - 1 service code
- 4 timers
- event log with 255 entries
- event printing feature
- monitoring using ContactID and other protocols
 - 2 monitoring stations numbers
- messaging
 - 4 telephone numbers
 - 1 voice message
 - 2 text messages
- incoming call answering
 - partition state check
 - system operation (with optional **MST-1** module)
- advanced telephone tone analysis:
 - TBR-21 compliant tone detection
 - intelligent redial attempts
 - programmable dialing sequence
- built-in 300 bps modem
- autodiagnostic features for basic system components
- on-board switching mode power supply
 - controlled battery charging
 - load battery testing
 - battery deep discharge protection



TECHNISCHE GEGEVENS

Voedingsspanning alarmsysteem ($\pm 10\%$)	12 V DC
Afmetingen print	142 x 102 mm
Bedrijfstemperatuur	-10...+55 °C
Hoofdprint voedingsvoltage ($\pm 15\%$)	18 V AC, 50-60 Hz

